

Amendments to the Claims

The following listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims

- 1 1. (Currently Amended) An apparatus comprising:
 - 2 a physical register file, in which data associated with instructions of a computer
 - 3 program are to be stored in an order that is independent of whether a processor
 - 4 executing the instructions is in a multithread (MT) mode or a single-thread (ST) mode,
 - 5 and in which physical registers are to be divided equally among a plurality of threads
 - 6 when operating in MT mode. mode; and
 - 7 a list of physical registers within the physical register file that are not allocated to
 - 8 a logical register, entries in the list being completely allocated to a first thread while the
 - 9 processor is in the ST mode and when the processor transitions from the ST mode to
 - 10 the MT mode, entries in the list being partitioned such that a first portion of the entries
 - 11 are allocated to a first thread and a second portion of the entries are allocated to a
 - 12 second thread.
- 1 2. (Currently Amended) The apparatus of claim 1 further comprising at least one
- 2 register allocation table (RAT) to indicate ~~allocation of the data~~ mapping relationships
- 3 from logical registers to physical registers within the physical register file.

1 3. (Cancelled)

1 4. (Currently Amended) The apparatus of ~~claim 3~~ claim 1 wherein when the processor
2 is in the ST mode, a first portion of all of the physical registers in the physical register
3 file are allocated to the first thread and a second portion of all of the physical registers in
4 the physical register file are ~~allocated to~~ reserved for the second thread ~~if the processor~~
5 ~~is in ST mode~~, the first portion of all of the physical registers being larger than the
6 second portion of all of the physical registers.

1 5. (Original) The apparatus of claim 4 wherein the second thread is dormant if the
2 processor is in ST mode.

1 6. (Currently Amended) The apparatus of claim 4 wherein the first portion of all of the
2 physical registers within the physical register file remain allocated to the first thread after
3 the processor transitions from the ST mode to the MT mode ~~MT mode~~ until instructions
4 associated with data within the first portion of all of the physical registers within the
5 physical register file are retired.

1 7. (Original) The apparatus of claim 6 wherein the physical registers associated with
2 the retired instructions are indicated within the list of physical registers.

1 8. (Previously Presented) An apparatus comprising:
2 first means for storing data for use by a microprocessor, the first means being
3 allocated equally among a plurality of threads during a second mode of operation of the
4 microprocessor and in an order that is independent of whether the microprocessor is in
5 the second mode of operation or a first mode of operation, in which only a single thread
6 is processed;
7 second means for allocating the logical registers to the physical
8 registers.

1 9. (Canceled)

1 10. (Previously Presented) The apparatus of claim 8 wherein the second means
2 comprises a register allocation table to indicate the allocation of the logical registers to
3 the physical registers.

1 11. (Previously Presented) The apparatus of claim 8 wherein the second means
2 comprises a plurality of register allocation tables to indicate the allocation of the logical
3 registers to the physical registers, each of the plurality of register allocation tables being
4 associated with a separate thread of instructions.

1 12. (Original) The apparatus of claim 11 wherein the first mode of operation is a
2 single thread mode and the second mode is a multiple-thread mode.

1 13. (Original) The apparatus of claim 12 wherein the first means is a register file
2 comprising a list of the physical registers that are not allocated to the logical registers.

1 14. (Previously Presented) The apparatus of claim 13 wherein, in the second mode
2 of operation, the sum of the number of physical registers in the list and the number of
3 logical registers associated with a single thread equals the number of physical registers
4 within the physical register file.

1 15. (Original) The apparatus of claim 14 wherein a first physical register is indicated
2 in the list after an instruction associated with data stored in the first physical register is
3 retired.

1 16. (Currently Amended) A system comprising:

2 a memory unit to store a first and second thread of instructions;

3 a processor to perform the first and second thread of instructions, the processor

4 ~~comprising~~ including:

5 ___a physical register file, in which data associated with instructions of a computer

6 program are to be stored in an order that is independent of whether a processor

7 executing the instructions is in a multithread (MT) mode or a single-thread (ST)

8 ~~mode, and in which physical registers are to be divided equally among a plurality of~~

9 ~~threads when operating in MT mode.~~ mode, and

10 a list of physical registers within the physical register file that are not allocated to

11 a logical register, entries in the list being completely allocated to a first thread while

12 the processor is in the ST mode and when the processor transitions from the ST
13 mode to the MT mode, entries in the list being partitioned such that a first portion of
14 the entries are allocated to a first thread and a second portion of the entries are
15 allocated to a second thread.

1 17. (Currently Amended) The system of claim 16 wherein the processor further
2 comprises at least one register allocation table (RAT) to indicate ~~allocation of the data~~
3 mapping relationships from logical registers to physical registers within the physical
4 register file.

1 18. (Cancelled)

1 19. (Currently Amended) The system of ~~claim 18~~ claim 16 wherein when the
2 processor is in the ST mode, a first portion of all of the physical registers in the physical
3 register file are allocated to the first thread and a second portion of all of the physical
4 registers in the physical register file are ~~allocated to~~ reserved for the second thread if
5 ~~the processor is in ST mode~~, the first portion of all of the physical registers being larger
6 than the second portion of all of the physical registers.

1 20. (Currently Amended) The system of claim 19 wherein the second thread is
2 dormant if the processor is in ~~ST mode~~ the ST mode.

1 21. (Currently Amended) The system of claim 19 wherein the first portion of all of the
2 physical registers within the physical register file remain allocated to the first thread after
3 the processor transitions from the ST mode to the MT mode ~~MT mode~~ until instructions
4 associated with data within the first portion of all of the physical registers within the
5 physical register file are retired.

1 22. (Original) The system of claim 21 wherein the physical registers associated with
2 the retired instructions are indicated within the list of physical registers.

1 23. (Currently Amended) A method comprising:
2 initializing a register allocation table (RAT) to map a first group of logical registers to
3 a second group of physical registers;
4 dividing a freelist of registers ~~in half~~ equally for each thread if a processor associated
5 with the free list is in multi-thread (MT) mode;
6 undividing the freelist of registers if the processor is in single-thread (ST) mode.

1 24. (Original) The method of claim 23 further comprising transitioning from ST mode
2 to MT mode, the second group of physical registers being interspersed throughout a
3 physical register file.

1 25. (Original) The method of claim 24 wherein the second group of physical registers
2 remain interspersed throughout the physical register file after the transition from ST to
3 MT mode.

1 26. (Original) The method of claim 23 further comprising transitioning from MT mode
2 to ST mode, the second group of physical registers being interspersed throughout a
3 physical register file.

1 27. (Original) The method of claim 26 wherein the second group of physical registers
2 remain interspersed throughout the physical register file after the transition from MT to
3 ST mode.

1 28. (Original) The method of 23 wherein the logical registers are allocated to the
2 physical registers independently of the relative position of the logical registers to each
3 other.

1 29. (Previously Presented) The method of claim 28 wherein, in MT mode, the sum of
2 the entries in the freelist and the number of logical registers associated with a single
3 thread equals the number of physical registers within the physical register file.

1 30. (Currently Amended) The method of claim 29 further comprising ~~a~~ including
2 including a first physical register in the freelist after an instruction associated with data
3 stored in the first physical register is retired.